

30-piece Alternator Tool Set (Art. 4248)

PRO +



- for removing the alternator pulleys
- includes special sockets, wrenches and bit sockets
- sockets for 3-hole-nuts, bolt circle 28 mm,
3x 4 mm pin, 38 mm drive
- sockets for 4-hole-nuts, bolt circle 26 mm,
4x 4 mm pin, 15 mm drive
- int. hex. sockets with hole for counterholding bits:
15x28 - 19x28 - 20x28 - 22x28 -
22x22 - 17x17 - 22x28 mm
- multi-tooth sockets with hole for counterholding bits:
33T x 15 mm - 17 mm x 33T - 33Z x 22 mm
- T-Star bits with 1/2" drive:
T50 x 200 mm - T50 x 140 mm
- Spline bit sockets with 1/2" drive:
M10 x 200 mm - M10 x 145 mm
- bits 75 mm long, 10 mm drive:
T-Star: T40 - T50
Spline: M8 - M10
Int. hex. socket: 8 mm - 10 mm
- 12 mm ratchet wrench
- bit sockets for use with ratchet wrench: spline
T50 x 65 mm - XZN M10 x 65 mm
- 1/2" bit sockets with fixed multi-point socket:
T50 x 115 mm - Spline M10 x 115 mm
with 33 teeth multi-point socket
- 3/8" bit socket with fixed multi-point socket:
Spline M10 x 90 mm

Technical modifications reserved - we are not responsible for issues while printing