

192-piece Socket Set, "Gear Lock", 1/4" + 3/8" + 1/2" (Art. 2247)



10 3/8

12.5 1/2

6.3 1/4



BGS
technic

PRO +



- "Gear Lock" profile sockets, provides universal use of 3-pt, 4-pt, 6-pt, 12-pt and E-type, for metric and inch sizes
- hardness and torque in accordance with DIN
- drive: 1/4", 3/8" and 1/2"
- reversible ratchets, fine toothed, 72 tooth, with quick release
- includes following tools:
 - **with 1/4" drive**
 - 1x reversible ratchet
 - 1x sliding bar
 - 1x extension bar 50 mm
 - 1x extension bar 100 mm
 - 1x universal joint
 - 1x spinner handle 150 mm
 - 13x sockets "Gear Lock" 4-4,5-5-5,5-6-7-8-9-10-11-12-13-14 mm
 - 7x deep sockets "Gear Lock" 4-5-6-7-8-9-10 mm
 - 5x E-type sockets E4-5-6-7-8
 - 1x bit holder for 1/4" bits
 - 6x cross slot bit sockets PH0-1-2, PZ0-1-2
 - 4x slot bit sockets 4-5.5-6.5-7 mm
 - 4x inner hex. bit sockets 3-4-5-6 mm
 - 8x T-star bit sockets (for Torx) T8-9-10-15-20-25-27-30
 - 8x T-star bit sockets (tamperproof) (for Torx) T8-9-10-15-20-25-27-30

- with 3/8" drive

- 1x reversible ratchet
- 1x extension bar 125 mm
- 1x universal joint
- 1x spark plug socket 18 mm
- 10x sockets "Gear Lock" 10-11-12-13-14-15-16-17-18-19 mm
- 6x deep sockets "Gear Lock" 10-11-12-13-14-15 mm
- 5x E-type sockets E10-11-12-14-16
- 1x bit holder for 8 mm bits

- with 1/2" drive

- 1x reversible ratchet
- 1x extension bar 125 mm
- 1x extension bar 250 mm
- 1x sliding bar adapter for 1/2" extension bar
- 1x bit holder for 8 mm bits
- 1x universal joint
- 2x spark plug sockets 16-21 mm
- 17x sockets "Gear Lock"
10-11-12-13-14-15-16-17-18-19-20-21-22-24-27-30-32 mm
- 5x deep sockets "Gear Lock" 16-17-18-19-22 mm
- 3x E-type sockets E18-20-24

- Bits with 8 mm drive

- 3x slot SL bits 8-10-12 mm
- 4x cross slot bits PH3-PH4-PZ3-PZ4
- 5x inner hex. bits 7-8-10-12-14 mm
- 6x T-star bits (for Torx) T40-45-50-55-60-70
- 6x T-star bits, tamperproof, (for Torx) T40-45-50-55-60-70

- Bits with 1/4" drive

- 10x T-star bits (for Torx) T5-6-7-10-15-20-25-27-30-40
- 8x T-star bits, tamperproof, (for Torx) T7-10-15-20-25-27-30-40
- 5x spline bits (for RIBE) M5-6-7-8-9
- 3x spline bits (for XZN) M5-6-8
- 8x TS-star bits TS10-15-20-25-27-30-40-45
- 4x cross slot bits PH3-PH4-PZ3-PZ4
- 2x inner hex. bits H2-2.5
- 7x L-type key set, inner hex.
1-1.5-2-2.5-3-4-5 mm