

Digital Multimeter, 3 1/2 Digit (Art. 9074)



- suitable for measurements in CAT II range
- 3 1/2 digit, 7 segments, 0.5" LCD
- indication for overflow, polarity and low battery voltage
- measuring ranges for resistance, AC voltage, DC voltage, diode voltage drop and hFE transistor measurements
- DC voltage measuring ranges:
 - 200 mV, resolution: 10uV, accuracy: $\pm 0.5\%$ +10digit
 - 2000 mV, resolution: 1mV, accuracy: $\pm 1\%$ +5digit
 - 20 V, resolution: 10mV, accuracy: $\pm 1\%$ +5digit
 - 200 V, resolution: 100 mV, accuracy: $\pm 1\%$ +5digit
 - 600V, resolution: 1V, accuracy: $\pm 1.2\%$ +5digit
- AC voltage measuring ranges:
 - 200 V, resolution: 10mV, accuracy: $\pm 0.5\%$ +10digit
 - 600V, resolution: 1V, accuracy: $\pm 0.5\%$ +10digit
- DC current measuring ranges:
 - 200 uA, resolution: 100nA, accuracy: $\pm 1.8\%$ +2digit
 - 2000 uA, resolution: 1uA, accuracy: $\pm 1.8\%$ +2digit
 - 20 mA, resolution: 10uA, accuracy: $\pm 1.8\%$ +2digit
 - 200 mA, resolution: 100uA, accuracy: $\pm 2\%$ +2digit
 - 10 A, resolution: 10mA, accuracy: $\pm 2\%$ +10digit
- resistance measurement ranges:
 - 200 Ohm, resolution: 0.1 mOhm, accuracy: $\pm 1\%$ +10digit
 - 2000 Ohm, resolution: 1 Ohm, accuracy: $\pm 2\%$ +4digit
 - 20 KOhm, resolution: 10 Ohm, accuracy: $\pm 2\%$ +4digit
 - 200 KOhm, resolution: 100 Ohm, accuracy: $\pm 2\%$ +4digit
 - 2000 KOhm, resolution: 1 KOhm, accuracy: $\pm 2\%$ +4digit
- operating temperature: 10°C ~ 40°C, 0~75% relative humidity

- power supply: 2x 1.5V AAA battery
- dimensions: (l)126 x (w)70 x (h)24 mm
- weight: 140g (incl. battery)